

SAFETY DATA SHEET

1. Identification

Product identifier: First Street Furniture Polish Lemon Scent

Other means of identification

SDS number: RE1000035735

Recommended restrictions

Product use: Coating

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: Smart & Final
Address: 5500 Sheila Street
Commerce, CA 90040
Telephone: 800-535-5053
Fax:

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol	Category 1
Gases under pressure	Liquefied gas

Health Hazards

Aspiration Hazard	Category 1
-------------------	------------

Environmental Hazards

Acute hazards to the aquatic environment	Category 3
Chronic hazards to the aquatic environment	Category 3

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.
May be fatal if swallowed and enters airways.
Harmful to aquatic life with long lasting effects.
Contains gas under pressure; may explode if heated.

Precautionary Statements

- Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid release to the environment.
- Response:** IF SWALLOWED: Immediately call a POISON CENTER/doctor/... Do NOT induce vomiting.
- Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up.
- Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Distillates (petroleum), hydrotreated light	64742-47-8	5 - <10%
White mineral oil (petroleum)	8042-47-5	1 - <5%
Butane	106-97-8	1 - <5%
Naphtha (petroleum), hydrotreated light	64742-49-0	1 - <5%
Propane	74-98-6	1 - <5%
Siloxanes and Silicones, di-Me	63148-62-9	1 - <5%
Heptane	142-82-5	1 - <5%
Cyclohexane, methyl-	108-87-2	0.1 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
- Inhalation:** Move to fresh air.
- Skin Contact:** Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

- Symptoms:** No data available.
- Hazards:** No data available.

Indication of immediate medical attention and special treatment needed

Treatment: No data available.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

Methods and material for containment and cleaning up: Stop the flow of material, if this is without risk. Absorb with sand or other inert absorbent.

Notification Procedures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Conditions for safe storage, including any incompatibilities: Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 1

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Distillates (petroleum), hydrotreated light - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2008)
Distillates (petroleum), hydrotreated light	REL	100 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Distillates (petroleum), hydrotreated light - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2008)
Distillates (petroleum), hydrotreated light	ST ESL	3,500 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
White mineral oil (petroleum) - Mist.	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
White mineral oil (petroleum) - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (01 2010)
White mineral oil (petroleum) - Mist.	TWA PEL	5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA	5 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
White mineral oil (petroleum) - Vapor.	AN ESL	100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL	1,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Butane	REL	800 ppm 1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	800 ppm 1,900 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	1,000 ppm	US. ACGIH Threshold Limit Values (03 2018)
	TWA	800 ppm 1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	AN ESL	3,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	7,100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA PEL	800 ppm 1,900 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL	66,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL	28,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Naphtha (petroleum), hydrotreated light	PEL	100 ppm 400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
	TWA PEL	300 ppm 1,350 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	STEL	400 ppm 1,800 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	TWA	100 ppm 400 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	REL	100 ppm 400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	ST ESL	3,500 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	100 ppm 400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Propane	REL	1,000 ppm 1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	1,000 ppm 1,800 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA	1,000 ppm 1,800 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Heptane	TWA	400 ppm 1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)

	STEL	500 ppm	2,000 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	REL	85 ppm	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	STEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	400 ppm		US. ACGIH Threshold Limit Values (02 2012)
	STEL	500 ppm		US. ACGIH Threshold Limit Values (02 2012)
	TWA	400 ppm	1,600 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		10,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		2,700 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		2,400 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	Ceil_Time	440 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA PEL	400 ppm	1,600 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	STEL	500 ppm	2,000 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	AN ESL		660 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Cyclohexane, methyl-	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	ST ESL		16,100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	400 ppm		US. ACGIH Threshold Limit Values (2008)
	AN ESL		1,610 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	400 ppm	1,600 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA PEL	400 ppm	1,600 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL		4,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	REL	400 ppm	1,600 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	AN ESL		400 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Benzene, ethyl-	TWA	100 ppm	435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	125 ppm	545 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		26,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		570 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		6,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		130 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	30 ppm	130 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2013)
	STEL	125 ppm	545 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	STEL	125 ppm	545 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	20 ppm		US. ACGIH Threshold Limit Values (12 2010)
	TWA PEL	5 ppm	22 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2013)
Cyclohexane	TWA	100 ppm		US. ACGIH Threshold Limit Values (2008)
	ST ESL		3,400 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	300 ppm	1,050 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	300 ppm	1,050 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)

	REL	300 ppm	1,050 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	300 ppm	1,050 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	300 ppm	1,050 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	AN ESL		340 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		100 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		1,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Hexane	TWA PEL	50 ppm	180 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA	50 ppm	180 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	50 ppm	180 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	500 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	REL	50 ppm	180 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	50 ppm		US. ACGIH Threshold Limit Values (2008)
	AN ESL		200 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		6,200 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		57 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		1,700 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Benzene, methyl-	STEL	150 ppm	560 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA PEL	10 ppm	37 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (02 2012)
	REL	100 ppm	375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	100 ppm	375 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	150 ppm	560 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	Ceiling	300 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	TWA	20 ppm		US. ACGIH Threshold Limit Values (2008)
	Ceiling	500 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	AN ESL		1,200 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	200 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX. CONC	500 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	ST ESL		4,500 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	STEL	150 ppm	580 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		1,200 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	100 ppm	375 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	AN ESL		320 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Benzene	REL	0.1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	1 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceiling	25 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	STEL	1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA A LV	0.5 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	AN ESL		1.4 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	0.5 ppm		US. ACGIH Threshold Limit Values (2008)
	STEL	25 ppm		US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	5 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000)

			(1989)
	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA PEL	1 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL	170 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	10 ppm	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	53 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	STEL	2.5 ppm	US. ACGIH Threshold Limit Values (2008)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	TWA	10 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX. CONC	50 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	AN ESL	4.5 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	Ceiling	50 ppm	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Benzene, ethyl- (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)
Hexane (2,5-Hexanedion, without hydrolysis: Sampling time: End of shift.)	0.5 mg/l (Urine)	ACGIH BEL (03 2018)
Benzene, methyl- (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL (03 2013)
Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL (03 2013)
Benzene (t,t-Muconic acid: Sampling time: End of shift.)	500 µg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene (S-Phenylmercapturic acid: Sampling time: End of shift.)	25 µg/g (Creatinine in urine)	ACGIH BEL (03 2013)

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

General information: Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection: Wear goggles/face shield.

Skin Protection

Hand Protection: No data available.

Other: No data available.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: When using do not smoke. Observe good industrial hygiene practices.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	Spray Aerosol
Color:	No data available.
Odor:	No data available.
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	-104.44 °C
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	275.788 - 413.682 hPa (20 °C) 689.47 - 827.364 hPa (50 °C)
Vapor density:	No data available.
Density:	No data available.
Relative density:	No data available.
Solubility(ies)	
Solubility in water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	2500 - 4500 mm ² /s

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
-------------	--------------------

Skin Contact: No data available.
Eye contact: No data available.
Ingestion: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.
Skin Contact: No data available.
Eye contact: No data available.
Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Distillates (petroleum), hydrotreated light	LD 50 (Rat): > 5,000 mg/kg
White mineral oil (petroleum)	LD 50 (Rat): > 5,000 mg/kg
Naphtha (petroleum), hydrotreated light	LD 50 (Rat): > 5,000 mg/kg
Heptane	LD 50 (Rat): > 5,000 mg/kg
Cyclohexane, methyl-	LD Lo (Rabbit): 4,000 - 4,500 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Distillates (petroleum), hydrotreated light	LD 50 (Rabbit): > 2,000 mg/kg
White mineral oil (petroleum)	LD 50 (Rabbit): > 2,000 mg/kg
Naphtha (petroleum), hydrotreated light	LD 50 (Rabbit): > 3,750 mg/kg
Heptane	LD 50 (Rabbit): > 2,000 mg/kg
Cyclohexane, methyl-	LD 50 (Rabbit): > 2,000 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Distillates (petroleum), hydrotreated light	LC 50: > 5 mg/l LC 50: > 20 mg/l
White mineral oil	LC 50 (Rat): > 5 mg/l

(petroleum)	LC 50: > 20 mg/l
Butane	LC 50 (Mouse): 1,237 mg/l
Naphtha (petroleum), hydrotreated light	LOAEL (Human): 2,400 mg/m3 LC 50 (Rat): > 7,630 mg/m3 LC 50: > 5 mg/l
Propane	LC 50 (Mouse): 1,237 mg/l
Heptane	LC 50 (Rat): > 29.29 mg/l
Cyclohexane, methyl-	LD 10 (Mouse): 40 - 50 mg/l LC 50 (Rat): > 26.3 mg/l

Repeated dose toxicity

Product: No data available.

Specified substance(s):

Distillates (petroleum), hydrotreated light	NOAEL (Rat(Female, Male), Inhalation): >= 24 mg/m3 Inhalation Experimental result, Key study NOAEL (Rat(Female), Oral, 70 - 147 d): 750 mg/kg Oral Experimental result, Key study
White mineral oil (petroleum)	NOAEL (Rat(Female, Male), Oral, 90 d): >= 20,000 ppm(m) Oral Experimental result, Key study NOAEL (Rabbit(Female, Male), Dermal): 1,000 mg/kg Dermal Read-across from supporting substance (structural analogue or surrogate), Key study LOAEL (Rat(Female, Male), Inhalation): 210 mg/m3 Inhalation Experimental result, Key study
Butane	NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
Naphtha (petroleum), hydrotreated light	LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg Oral Read- across based on grouping of substances (category approach), Key study NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal Experimental result, Supporting study NOAEL (Rat(Female, Male), Inhalation): 10,000 mg/m3 Inhalation Experimental result, Key study
Propane	NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
Heptane	NOAEL (Rat(Male), Inhalation): 12,470 mg/m3 Inhalation Experimental result, Key study
Cyclohexane, methyl-	LOAEL (Rat(Female, Male), Oral, 28 d): 1,000 mg/kg Oral Experimental result, Key study NOAEL (Rat(Female, Male), Oral, 28 d): 250 mg/kg Oral Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation): 1,600 mg/m3 Inhalation Experimental result, Key study

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Distillates (petroleum), hydrotreated light	in vivo (Rabbit): Not irritant Experimental result, Key study
White mineral oil (petroleum)	in vivo (Rabbit): Not irritant Experimental result, Key study

Heptane	in vivo (Rabbit): Irritating Read-across based on grouping of substances (category approach), Key study
Cyclohexane, methyl-	in vivo (Rabbit): Not irritant Experimental result, Weight of Evidence study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Distillates (petroleum), hydrotreated light	Rabbit, 24 - 72 hrs: Not irritating
White mineral oil (petroleum)	Rabbit, 24 - 72 hrs: Not irritating
Naphtha (petroleum), hydrotreated light	Rabbit, 24 - 72 hrs: Not irritating
Heptane	Rabbit, 24 - 72 hrs: Not irritating
Cyclohexane, methyl-	Rabbit, 0.5 - 168 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

Distillates (petroleum), hydrotreated light	Skin sensitization:, in vivo (Guinea pig): Non sensitising
White mineral oil (petroleum)	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Naphtha (petroleum), hydrotreated light	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Heptane	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Cyclohexane, methyl-	Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

Product: No data available.

Specified substance(s):

Cyclohexane, methyl- May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specified substance(s):

Heptane Narcotic effect. - Category 3 with narcotic effects.
Cyclohexane, methyl- Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Specified substance(s):
Cyclohexane, methyl- Category 1

Aspiration Hazard

Product: No data available.

Specified substance(s):
Distillates (petroleum), hydrotreated light May be fatal if swallowed and enters airways.
White mineral oil (petroleum) May be fatal if swallowed and enters airways.
Naphtha (petroleum), hydrotreated light May be fatal if swallowed and enters airways.
Heptane May be fatal if swallowed and enters airways.
Cyclohexane, methyl- May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):
Distillates (petroleum), hydrotreated light LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 2.9 mg/l Mortality
NOAEL (Oncorhynchus mykiss, 96 h): 2 mg/l Experimental result, Key study

White mineral oil (petroleum) NOAEL (Oncorhynchus mykiss, 96 h): >= 100 mg/l Experimental result, Key study
LL 50 (Oncorhynchus mykiss, 96 h): > 100 mg/l Experimental result, Key study

Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Naphtha (petroleum), hydrotreated light LC 50 (96 h): 8.41 mg/l Experimental result, Key study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Siloxanes and Silicones, di-Me LC 50 (Redear sunfish (Lepomis microlophus), 96 h): 26.27 - 56.73 mg/l Mortality

Heptane LC 50 (Mozambique tilapia (Tilapia mossambica), 96 h): 375 mg/l Mortality

Cyclohexane, methyl- LC 50 (Oryzias latipes, 96 h): 2.07 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):
Distillates (petroleum), hydrotreated light EC 50 (Daphnia magna, 24 h): 4.6 mg/l Experimental result, Key study
NOAEL (Daphnia magna, 48 h): 0.3 mg/l Experimental result, Key study

	EC 50 (Daphnia magna, 48 h): 1.4 mg/l Experimental result, Key study
White mineral oil (petroleum)	NOAEL (Daphnia magna, 48 h): >= 100 mg/l Experimental result, Key study
Butane	LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study
Naphtha (petroleum), hydrotreated light	EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study
Siloxanes and Silicones, di-Me	LC 50 (Water flea (Daphnia magna), 48 h): 44.5 mg/l Mortality
Heptane	EC 50 (Daphnia magna, 48 h): 1.5 mg/l Experimental result, Key study
Cyclohexane, methyl-	EC 50 (Daphnia magna, 48 h): 0.326 mg/l Experimental result, Key study ED 0 (Daphnia magna, 48 h): 0.037 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish

Product:	No data available.
Specified substance(s): Distillates (petroleum), hydrotreated light	NOAEL (Oncorhynchus mykiss): 0.098 mg/l QSAR QSAR, Key study
White mineral oil (petroleum)	NOAEL (Oncorhynchus mykiss): >= 1,000 mg/l QSAR QSAR, Supporting study
Naphtha (petroleum), hydrotreated light	EC 50 (Daphnia magna): 10 mg/l Other, Key study NOAEL (Daphnia magna): 2.6 mg/l Other, Key study
Heptane	NOAEL (Oncorhynchus mykiss): 1.284 mg/l QSAR QSAR, Key study

Aquatic Invertebrates

Product:	No data available.
Specified substance(s): Distillates (petroleum), hydrotreated light	NOAEL (Daphnia magna): 1.2 mg/l Experimental result, Key study EC 50 (Daphnia magna): 0.81 mg/l Experimental result, Key study
White mineral oil (petroleum)	NOAEL (Daphnia magna): >= 1,000 mg/l QSAR QSAR, Supporting study
Naphtha (petroleum), hydrotreated light Heptane	EC 50 (Daphnia magna): 10 mg/l Experimental result, Key study NOAEL (Daphnia magna): 2.6 mg/l Experimental result, Key study NOAEL (Daphnia magna): 0.17 mg/l Read-across based on grouping of substances (category approach), Key study EC 50 (Daphnia magna): 0.23 mg/l Read-across based on grouping of substances (category approach), Key study

Toxicity to Aquatic Plants

Product:	No data available.
-----------------	--------------------

Persistence and Degradability

Biodegradation

Product:	No data available.
-----------------	--------------------

Specified substance(s):

Distillates (petroleum), hydrotreated light	61 % Detected in water. Experimental result, Supporting study
White mineral oil (petroleum)	31 % (28 d) Detected in water. Read-across from supporting substance (structural analogue or surrogate), Supporting study
Butane	100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study
Naphtha (petroleum), hydrotreated light	90.35 % (28 d) Detected in water. Experimental result, Supporting study
Propane	100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study
Heptane	70 % Detected in water. Experimental result, Key study
Cyclohexane, methyl-	> 0 % (28 d) Detected in water. Experimental result, Weight of Evidence study > 0 % (28 d) Detected in water. Experimental result, Weight of Evidence study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Naphtha (petroleum), hydrotreated light	Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study
Heptane	Bioconcentration Factor (BCF): 552 Aquatic sediment Estimated by calculation, Key study
Cyclohexane, methyl-	Cyprinus carpio, Bioconcentration Factor (BCF): > 95 - < 321 Aquatic sediment Experimental result, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Naphtha (petroleum), hydrotreated light	Log Kow: > 2.4 - < 5.7 23 °C Yes Experimental result, Key study Log Kow: 2.2 - 5.2 23 °C Yes Experimental result, Key study Log Kow: 2.2 - 6.1 23 °C Yes Experimental result, Key study
---	---

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Distillates (petroleum), hydrotreated light	No data available.
White mineral oil (petroleum)	No data available.
Butane	No data available.
Naphtha (petroleum), hydrotreated light	No data available.
Propane	No data available.
Siloxanes and Silicones, di-Me	No data available.
Heptane	No data available.
Cyclohexane, methyl-	No data available.

Other adverse effects: Harmful to aquatic life with long lasting effects.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local laws.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	–
Packing Group:	II
Marine Pollutant:	No
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.

IMDG

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2
Label(s):	–
EmS No.:	
Packing Group:	–
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.

IATA

UN Number:	UN 1950
Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es):	
Class:	2.1
Label(s):	–
Packing Group:	–
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Benzene	respiratory tract irritation Central nervous system Blood Skin Flammability Cancer Aspiration Eye

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Butane	lbs. 100
Propane	lbs. 100
Heptane	lbs. 100
Cyclohexane, methyl-	lbs. 100
Benzene, ethyl-	lbs. 1000
Cyclohexane	lbs. 1000
Hexane	lbs. 5000
Benzene, methyl-	lbs. 1000
Benzene	lbs. 10

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

- Fire Hazard
- Immediate (Acute) Health Hazards
- Flammable aerosol
- Aspiration Hazard

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Distillates (petroleum), hydrotreated light		

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Distillates (petroleum), hydrotreated light	
Butane	lbs. 100
Propane	lbs. 100
Heptane	lbs. 100
Cyclohexane, methyl-	lbs. 100
Benzene, ethyl-	lbs. 1000
Cyclohexane	lbs. 1000
Hexane	lbs. 5000
Benzene, methyl-	lbs. 1000
Benzene	lbs. 10

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Distillates (petroleum), hydrotreated light	10000 lbs
White mineral oil (petroleum)	10000 lbs
Butane	10000 lbs
Naphtha (petroleum),	10000 lbs

hydrotreated light	
Propane	10000 lbs
Siloxanes and Silicones, di-Me	10000 lbs
Heptane	10000 lbs
Cyclohexane, methyl-	10000 lbs
Benzene, ethyl-	10000 lbs
Cyclohexane	10000 lbs
Hexane	10000 lbs
Benzene, methyl-	10000 lbs
Benzene	10000 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Benzene, ethyl-	Carcinogenic. 05 2011
Hexane	Male reproductive toxin. 12 2017
Benzene, methyl-	Developmental toxin. 03 2008
Benzene	Developmental toxin. 03 2008
Benzene	Carcinogenic. 05 2011
Benzene	Male reproductive toxin. 03 2008

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Distillates (petroleum), hydrotreated light
White mineral oil (petroleum)
Butane
Naphtha (petroleum), hydrotreated light
Propane
Heptane

US. Massachusetts RTK - Substance List

No ingredient regulated by MA Right-to-Know Law present.

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Distillates (petroleum), hydrotreated light
White mineral oil (petroleum)
Butane
Naphtha (petroleum), hydrotreated light
Propane
Heptane

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

Distillates (petroleum),
hydrotreated light

Stockholm convention

Distillates (petroleum),
hydrotreated light

Rotterdam convention

Distillates (petroleum),
hydrotreated light

Kyoto protocol

Inventory Status:

Australia AICS:	On or in compliance with the inventory
Canada DSL Inventory List:	On or in compliance with the inventory
EINECS, ELINCS or NLP:	Not in compliance with the inventory.
Japan (ENCS) List:	Not in compliance with the inventory.
China Inv. Existing Chemical Substances:	On or in compliance with the inventory
Korea Existing Chemicals Inv. (KECI):	On or in compliance with the inventory
Canada NDSL Inventory:	Not in compliance with the inventory.
Philippines PICCS:	Not in compliance with the inventory.
US TSCA Inventory:	On or in compliance with the inventory
New Zealand Inventory of Chemicals:	On or in compliance with the inventory
Japan ISHL Listing:	Not in compliance with the inventory.
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.
Mexico INSQ:	Not in compliance with the inventory.
Ontario Inventory:	On or in compliance with the inventory
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory

16. Other information, including date of preparation or last revision

Issue Date: 08/15/2019

Revision Information: No data available.

Version #: 1.2

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.